

Chemical-Soil Stabilization for Runway Shoulder Widening at Singapore Changi Airport

Koh Ming Sue

Civil Aviation Authority of Singapore

Koh_Ming_Sue@caas.gov.sg

Lim Boon Chai

Civil Aviation Authority of Singapore

Lim_Boon_Chai@caas.gov.sg

Dr Wu Dong Qing

Chemilink Technologies Group, Singapore

wu@chemilink.com.sg

Contents

- 1. Introduction**
- 2. Evaluation Criteria**
- 3. Chemical–Soil Stabilization**
- 4. Runway Shoulder Widening Process**
- 5. Quality Control**
- 6. Benefits of Chemical–Soil Stabilization in the Airport Environment**
- 7. Conclusions**
- 8. Acknowledgements**
- 9. References**

1. Introduction


- * **Airbus A380 is the largest commercial aircraft built to date.**
- * **The runway shoulders have to be widened to support A380 operations.**



Fig. 1. Airports Ready for the Airbus A380

- * **SIA is the launch customer for A380.**
- * **CAAS has begun planning for upgrading. including runway shoulders widening since the late 1990's.**

1. Introduction



- * Existing runway width: 66m
- * Widened runway width: 75m
- * How to do widening in a busy airport?

2. Evaluation Criteria

- * CAAS evaluated various technical proposals with following major considerations:**

2-1 Ability to Meet Airport Operational Restrictions

2-2 Construction Speed

2-3 Structural Design

2-4 Environmental Impact

2-5 Cost Effectiveness

2. Evaluation Criteria

* Final Decision

☒ Replacement method – Conventional pavement construction

☒ Non-replacement method – In-situ chemical-soil stabilization




Fig. 3. Cross Section of Existing Runway Shoulders vs. Widened Section by Chemical Stabilization

- 👍 A polymer modified cementitious chemical stabilizing agent be used for base course topped by asphalt concrete
- 👍 Offering comprehensive advantages and benefits

3. Chemical–Soil Stabilization

- * Definition:**

“Mixing proper chemicals with in-situ soils to improve/strengthen the soil properties through chemical reactions for engineering purposes.”

- * The selected chemical stabilizing agent has successfully been applied in Asia, especially in South-East Asia region for more than 10 years.**

- * A specially designed version of chemical agent was used to stabilize:**

- ☐ **Clayey soils**
- ☐ **Sandy soils**
- ☐ **Crushed stones**
- ☐ **Their mixtures**

3. Chemical–Soil Stabilization

* **Design requirements:**

- ☐ $UCS \geq 1.5 \sim 2.0 \text{ MPa (7-d)}$
- ☐ $CBR \geq 90\% (7\text{-d})$
- ☐ $M_R \geq 3,000 \text{ MPa (28-d)}$

* **Chemical Dosage : 3.75% for all widened base course**


* **Major Stabilization Process**

1st step: Spreading

2nd step: Mixing

3rd step: Compaction

4. Runway Shoulder Widening Process



Notes:

Runway Closure Time : 1:00am ~ 7:00am

Effective Construction Time : 2:00am ~ 6:00am

Average Area per 4 Working Hours: 250m by 4.5m or 225m²/hour

Fig. 4. Typical Construction Procedure of New Shoulders

4. Runway Shoulder Widening Process



Photo 1. Excavation



Photo 2. Spreading

4. Runway Shoulder Widening Process



Photo 3. In-Situ Mixing



Photo 4. Compaction

4. Runway Shoulder Widening Process



Photo 5. Paving Asphalt Concrete



Photo 6. Completion of Widening

4. Runway Shoulder Widening Process

**Table 1. Comparison of Planned and Actual Construction Period
for Runway Shoulders Construction
using Chemical Soil Stabilization Method**

| Runway | Planned Construction Period | Actual Construction Period | Actual Working Days | Remarks |
|--------|-----------------------------|--------------------------------|---------------------|-------------------------------------|
| I | 90 days | (31/05/05~11/07/05) 42 days | 31 days | Ave. 208 m/day |
| II | 90 days | (08/03/05~29/04/05) 53 days | 29 days | Ave. 226 m/day |
| I & II | 180 days | 95 days | 60 days | Ave. 217 m/day (Total:13kmx4.5m) |

5. Quality Control




Photo 7. Spreading Rate Check



Photo 8. Preparations of Specimens



Photo 9. UCS Test



Photo 10. CBR Test



Photo 11. Nuclear Density Test



Photo 12. Resilient Modulus Test

5. Quality Control





Fig. 5. UCS and CBR Testing Results



PROJECT RECORD

CAAS Permit No.: FPT/T1-065/05; FPT/T1-072/05



—Design & Build Contract for Widening of Runway

Shoulders & Associated Works at Singapore Changi Airport

(CAAS Project — CAA000/EN/NLA/2004/1)

INSTEK HOLDING PET LTD
36 TANJONG PENJURU, SINGAPORE 609031

TEL: 62522201 FAX: 62527886

<http://www.chemilink.com.sg>

6. Benefits of Chemical–Soil Stabilization in the Airport Environment

| Comparison Item (Daily basis and for base course only) | Conventional Replacement Method | Chemical-Soil Stabilization |
|---|---------------------------------------|---------------------------------------|
| Transportation (in & out, 10t truck) | > 100 trips | About 20 trips |
| Construction Rate (by 4.5M) | < 75M | Average: 250M |
| Security Clearance Time | 9 hours | Within limited and acceptable time |

* Chemical-Soil Stabilization

- ☐ Manpower: < 50 workheads
- ☐ Machinery/ Vehicles: < 20 units
- ☐ Re-opening time: 30 minutes

* 2.5 months ahead of the 6 months schedule

6. Benefits of Chemical–Soil Stabilization in the Airport Environment

- ❖ Better Environment Protection
- ❖ Limited Disturbances to Airport Operations
- ❖ Higher Airport Safety Assurances
- ❖ Simple and Faster Construction and Less Materials Transportation
- ❖ Better Technical Performances
- ❖ Cost Saving and Overall Cost Effectiveness



7. Conclusions

- 1) Widening has successfully been completed for Singapore Changi International Airport ---One of the 1st international airports to be ready for A380
- 2) Comprehensive project planning and methodology evaluation are critical for the smooth and on-time project completion.
- 3) The Chemical-Soil Stabilization Method is applicable with significant advantages and benefits
- 4) Technical performance to-date is satisfactory

Acknowledgements

- ❑ Civil Aviation Authority of Singapore (CAAS)
- ❑ Mr. Fong Kok Wai, Director (Development & Engineering),
CAAS

Thanks for Your Attention!





RUNWAY 2 AFTER 17 MONTHS




RUNWAY 2 AFTER 17 MONTHS



RUNWAY 1 AFTER 14 MONTHS


2-1 Ability to Meet Airport Operational Restrictions

- ☐ **One of busiest airports in the world with 2 runways**
- ☐ **Limited runway closure time from 1:00 am to 7:00 am**
- ☐ **Effective construction time is only about 4 hours**
- ☐ **Runways re-opening within 30 minutes**




2-2 Construction Speed

- ☐ **Higher construction unit rate**
- ☐ **Shorter project duration**
- ☐ **Safer construction activities**




2-3 Structural Design

- ☐ **ICAO requirements**
- ☐ **Latest recommendation from Airbus**
- ☐ **Sub-grade conditions – reclaimed land**
- ☐ **Proven technology and product in tropical region with a long history**



2-4 Environmental Impact

- ☐ **Less excavation and backfilling**
- ☐ **Less ground movements caused by vehicles, machines and manpower**
- ☐ **Less airport control and coordination works**
- ☐ **Environment friendly**



2-5 Cost Effectiveness

❖ Overall Costs

- ❑ Construction cost & related costs
- ❑ Long-term maintenance costs and related costs

